GIGABYTE B760 GAMING X AX Motherboard - Supports Intel Core 14th Gen CPUs, 8+1+1 Phases Digital VRM, up to 7600MHz DDR5 (OC), 3xPCle 4.0 M.2, Wi-Fi 6E, 2.5GbE LAN, USB 3.2 Gen 2

Brand: GIGABYTE Product code: B760 GAMING X AX

Product name: B760 GAMING X AX Motherboard - Supports Intel Core 14th Gen CPUs, 8+1+1 Phases Digital VRM, up to 7600MHz DDR5 (OC), 3xPCle 4.0 M.2, Wi-Fi 6E, 2.5GbE LAN, USB 3.2 Gen 2

 ${\tt B760~GAMING~X~AX~Motherboard~-} \ {\tt Supports~Intel~Core~14th~Gen~CPUs}, \ 8+1+1~{\tt Phases~Digital~VRM}, \ {\tt up~to~CPUs}, \ {\tt Sequence}, \ {\tt Sequence}$ 7600MHz DDR5 (OC), 3xPCle 4.0 M.2, Wi-Fi 6E, 2.5GbE LAN, USB 3.2 Gen 2

GIGABYTE B760 GAMING X AX Motherboard - Supports Intel Core 14th Gen CPUs, 8+1+1 Phases Digital VRM, up to 7600MHz DDR5 (OC), 3xPCle 4.0 M.2, Wi-Fi 6E, 2.5GbE LAN, USB 3.2 Gen 2:

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge





Processor			Rear panel I/O ports		
Processor manufacturer *		Intel	WiFi-AP antenna jack	2	
Processor socket *		LGA 1700	USB connector type	USB Type-A, USB Type-C	
Compatible processor series *		Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold LGA 1700	Network		
			Ethernet LAN	✓	
Supported processor sockets			Ethernet interface type	2.5 Gigabit Ethernet	
		LGA 1700	Wi-Fi *	✓	
Memory Supported memory types * DDR5-SDRAM			Top Wi-Fi standard	Wi-Fi 6E (802.11ax)	
Number of memory slots * Memory slots type Memory channels ECC compatibility	4 DIMM Dual-channel ECC & Non-ECC		Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)	
Supported memory clock speeds	4000,4800,5200,5400, MHz	,5600,5800,6000,6200,6400,6600,6800,7000,7200,7400,7600	WLAN controller model	Intel Wi-Fi 6E AX211	
Supported memory clock speed (max)	7600 MHz		Bluetooth	✓	
Maximum internal memory * Unbuffered memory	256 GB ✓		Bluetooth version	5.2	
Storage controllers			Features		
Supported storage drive types		HDD & SSD	Motherboard chipset *	Intel B760 Express	
Supported storage d	rive interfaces *	M.2, SATA III	Audio output channels *	7.1 channels	
Number of HDDs supported		4	Product colour	Brown	
Number of storage drives supported		7	PC health monitoring	Fan, Temperature, Voltage, Water cooling	
RAID support		0, 1, 5, 10	Component for *	PC	
RAID levels			Motherboard form factor *	ATX	
Graphics			Motherboard chipset family *	Intel	
Parallel processing technology support *		Not supported	Windows operating systems supported	Windows 10 x64, Windows 11 x64	
Maximum resolution		4096 x 2304 pixels	Expansion slots		
HDCP		✓	PCI Express x16 (Gen 4.x) slots	1	
DirectX version		12.0	Number of M.2 (M) slots	3	
			1st M.2 largest key size	22110	
			ISCHILL MIGCSCREY SIZE	22110	

Internal I/O		Expansion slots	
USB 2.0 connectors *	2	•	
USB 3.2 Gen 1 (3.1 Gen 1)		1st M.2 highest PCI Express generation	4.0
connectors *	1	2nd M.2 largest key size	22110
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	1	2nd M.2 highest PCI Express generation	4.0
Number of SATA III connectors *	4	3rd M.2 largest key size	22110
Total number of SATA connectors	4	3rd M.2 highest PCI Express generation	4.0
S/PDIF out connector	✓		
Front panel audio connector	/	BIOS	
Front panel connector	/	BIOS type *	UEFI AMI
ATX Power connector (24-pin)	✓	BIOS memory size ACPI version	256 Mbit 5.0
CPU fan connector	✓	Clear CMOS jumper	J.0 ✓
EPS power connector (8-pin)	✓	Desktop Management Interface	•
TPM connector	✓	(DMI) version	2.7
Serial port headers	1	System Management BIOS	2.7
12V power connector	✓	(SMBIOS) version	2.7
RGB LED pin header	✓	Logistics data	
Rear panel I/O ports		Country of origin	China
USB 2.0 ports quantity *	5	Products per shipping (inner) case	1 pc(s)
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	Battery	
ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C		Battery weight	3 g
ports quantity *	1	Lithium weight per battery	0.07 g
USB 3.2 Gen 2 (3.1 Gen 2) Type-A	1	Number of battery cells Battery technology	1 Lithium-Manganese Dioxide
ports quantity *			5
ports quantity * Ethernet LAN (RJ-45) ports *	1		(LiMnO2)
•	1	Battery type	5
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version	1 2.0	Battery type Packaging data	(LiMnO2)
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity	1 2.0 1	Battery type Packaging data Package width	(LiMnO2) CR2032
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version	1 2.0 1 1.2	Battery type Packaging data Package width Package depth	(LiMnO2) CR2032 335 mm 270 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Packaging data Package width Package depth Package height	(LiMnO2) CR2032 335 mm 270 mm 80 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version	1 2.0 1 1.2	Packaging data Package width Package depth Package height Package weight	(LiMnO2) CR2032 335 mm 270 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth Height	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth Height Packaging content	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg 305 mm 244 mm 35 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth Height Packaging content Cables included	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg 305 mm 244 mm 35 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth Height Packaging content Cables included Batteries included	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg 305 mm 244 mm 35 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth Height Packaging content Cables included Batteries included Bundled software	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg 305 mm 244 mm 35 mm
Ethernet LAN (RJ-45) ports * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Headphone outputs	1 2.0 1 1.2 6	Battery type Packaging data Package width Package depth Package height Package weight Weight & dimensions Width Depth Height Packaging content Cables included Batteries included	(LiMnO2) CR2032 335 mm 270 mm 80 mm 19 kg 305 mm 244 mm 35 mm





4719331851774

0889523035849



889523035849

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.