



LCD DISPLAY

VX2758A-2K-PRO

Key Features

- SuperClear® IPS panel
- 170Hz Refresh rate delivers fluid visuals
- 2K QHD resolution for incredible detail
- Rapid 1ms MPRT for crisp image
- AMD FreeSync™ eliminates screen tearing and reduce stuttering



Product Description

Experience immersive entertainment with the ViewSonic VX2758A-2K-PRO gaming monitor. Its high 170Hz refresh rate guarantees ultra-smooth animations, while the rapid 1ms MPRT response time delivers smooth visuals and minimal input lag, making it perfect for fast-paced gaming. Featuring AMD FreeSync™ technology to eliminate screen tearing and stuttering for seamless gaming experiences, this monitor also boasts ViewSonic's exclusive ViewMode™ presets, delivering stunning visuals optimized for heart-pounding gaming, captivating entertainment, creative editing, and beyond. The monitor is complete with versatile connectivity options, featuring DisplayPort and two HDMI inputs.

Visit Uswww.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	170
Variable Refresh Rate Technology:	FreeSync
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 95% coverage (Typ) NTSC: 97% size (Typ) sRGB: 137% size (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1

Power in:	3-pin Socket (IEC C14 / CEE22)
-----------	--------------------------------

POWER

Eco Mode (Conserve):	16W
Eco Mode (optimized):	20W
Consumption (typical):	26W
Consumption (max):	35W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Up, Right, Down, Left, Power
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 31 ~ 215KHz, DisplayPort (v1.4): 30 ~ 252KHz
Frequency Vertical:	HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 170Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	10.8
Net Without Stand (lbs):	9.8
Gross (lbs):	14

WEIGHT (METRIC)

Net (kg):	4.9
Net Without Stand (kg):	4.5
Gross (kg):	6.4

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	27.8 x 18.5 x 5
Physical (in.):	24.18 x 17.85 x 7.22
Physical Without Stand (in.):	24.18 x 14.4 x 1.85

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	706 x 471 x 128
Physical (mm):	614.1 x 453.35 x 183.3
Physical Without Stand (mm):	614.1 x 365.65 x 47.05

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA
PACKAGE CONTENTS:	VX2758A-2K-PRO x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market



Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

